

Wormwielkast VF44 voet A i=14 motorflens P63/B14 positie B3

Bonfiglioli worm gearboxes

VF-series worm gearbox with IEC motor flange (P-version) from manufacturer Bonfiglioli Riduttori are available in 3 foot versions (mounting version A, N, V), shaft mounted version (mounting version P) and side flange (mounting versions F, FA, FC, FR dependent of size).

Manufacturer code	VF44 A 14 P63/B14 B3
Manufacturer	Bonfiglioli Riduttori
Serie code reductor	VF - Worm gearbox
IEC flange type	B14
IEC flange size	63
Type code gearbox	VF044
Gearbox version	A - Foot horizontal worm shaft top
Type of gearbox input	P - IEC flange
Mounting position gearbox	B3
Output shaft diameter	18 mm
Input power	0.18 kW
Output torque gearbox	14 Nm
Safety factor	2.1
Input speed gearbox	1400 min-1
Ratio	14
Output speed gearbox	100 min-1
Angular backlash	0.00728 rad
Angular backlash tolerance	±0.00145 rad
Moment of inertia gearbox	0.000023 kgm ²
Dynamic efficiency	81 %
Static efficiency	60 %
Dynamic reversible	Yes
Static reversible	Yes
Weight gearbox	2 kg



